



P15 Series 900 MHz

890-942 MHz - 140 Watts Output Power

Frequency Range:	890-942 MHz
Operating Voltage:	+13.8 VDC
Current Draw:	43 Amperes (Max)
Duty Cycle:	100%
Power Input:	See chart below
Power Output:	140 Watts, set at factory
Spurious & Harmonics:	Meets FCC Requirements
Input/Output Impedance:	50 ohms (Nominal)
Load VSWR Tolerance:	VSWR Protected above 2.5:1
Input/Output Connector:	Type 'N' Female
Cooling Method:	Fan Forced Air Over Heat sinks
Operating Temp. Range:	-30 ⁰ C to +60 ⁰ C
Storage & Transport:	-40 ⁰ C to +70 ⁰ C
Humidity:	80% at +40 ⁰ C (non-condensing)
Altitude:	10,000 feet maximum

SIZE

Vertical Mounting:	10.0"
Horizontal Mounting:	19.0"
Depth:	6.0"
Weight:	14 pounds nominal

POWER INPUT RANGE

<u>Model Description</u>	<u>Required Power In</u>	<u>Power Output</u>
P15-R1LW1-C6-001	100-200 mW	140 W
P15-R2LW1-C6-001	200-500 mW	140 W
P15-R5LW1-C6-001	500 mW-1 W	140 W
P15-1LW1-C6-001	1-2 W	140 W
P15-2LW1-C6-001	2-5W	140 W
P15-5LW1-C6-001	5-10 W	140 W
P15-10LW1-C6-001	10-20 W	140 W
P15-20LW1-C6-001	20-50 W	140 W

Crescend Technologies, LLC · 140 E. State Parkway · Schaumburg, IL 60173
 Phone: (800) USA-MADE / (847) 908-5400 Fax: (847) 908-5408 · www.crescendtech.com

These specifications are subject to change without notice.